

# Moffett

## Model range at a glance

	Lift Capacity (t)	Drive Wheels	4-way Option	
<b>M1</b>	1.5	1, 3	N/A	<p>The M1 ideally operates on paved surfaces and has a lift capacity of 1.5 tonnes. This machine is specifically used in the distribution of food and beverage, insulation materials, bottled gas, chemicals and consumer goods distribution.</p> <p><b>Food &amp; beverage, insulation, bottled gas, consumer goods distribution</b></p>  
<b>M2</b>	2	1, 3	✓	<p>The M2 is a walk behind machine suitable for operation on paved and firm off-road surfaces and has a lift capacity of 2 tonnes. This machine is available in one and three wheel drive and 4-way mode. The M2 is used in the food and beverage and gas industries, carpet delivery and for general palletised goods.</p> <p><b>Food &amp; beverage, timber, gas, palletised goods and carpet delivery</b></p>  
<b>M3</b>	2	1, 3	✓	<p>The M3 has a 2 tonne lift capacity and is best suited to paved surfaces or firm off-road conditions. This machine is available in one and three wheel drive and 4-way mode. The M3 is mostly used in agriculture, food and beverage, extrusion industries and window and door delivery.</p> <p><b>Food &amp; beverage, windows and doors, extrusions, agricultural feeds, fertiliser</b></p>  
<b>M4</b>	2 to 2.5	1, 3	✓	<p>Capable of driving on almost all surfaces, the M4 is a highly versatile machine and has a lift capacity of either 2 or 2.5 tonnes. Available in one and three wheel drive and 4-way mode, the M4 is mostly used in the waste industry and recycling of materials, industrial gas, chemicals and the agriculture industries.</p> <p><b>Recycling, industrial gas, chemicals, agriculture, windows and doors, motorbikes</b></p>  
<b>M5</b>	2 to 2.5	3	✓	<p>The M5 range is available in three wheel drive or 4-way mode has a lift capacity of either 2 or 2.5 tonnes. The M5 works competently on both paved surfaces and rough terrain. Applications for this machine include building materials, animal feed, industrial gas and timber.</p> <p><b>Building materials, animal feed, industrial gas, timber, scaffolding, turf</b></p>  
<b>M6</b>	2.5	3	✓	<p>The M6 travels effortlessly on almost any surface and has a lift capacity of 2.5 tonnes. Available with three wheel drive or in 4-way mode, this machine is mostly applied to the building materials and timber industries, as well as the rescue services and military operations.</p> <p><b>Building materials, timber, rescue services, military</b></p>  
<b>M8</b>	2.5 to 3.5	3	✓	<p>Designed for a wide range of commercial and industrial applications, the M8 has a lift capacity from 2.5 to 3.5 tonnes. Available in three wheel drive and 4-way mode, the M8 is suitable for use on paved and rough conditions. Typical applications for the M8 include building materials, animal feed, agriculture, roofing, scaffolding and emergency services.</p> <p><b>Building materials, animal feed, agriculture, roofing, scaffolding and emergency services</b></p>  
<b>M9</b>	2.3	3	N/A	<p>Low overall height and three wheel drive ensure easy access and good manoeuvrability in the tough environment of the poultry house. The M9 has a lift capacity up to 2.3 tonnes.</p> <p><b>Poultry industry, NATO / military service</b></p>  

Delivering even more

# Moffett

## Options at a glance

Model	Moving mast	Static mast	Reach forks	Pantograph mast	Super reach	Load backrest	Fork positioner	Hydraulic attachments	Fork Options	Colour	Enclosed cab	Front stabilisers	Retractable legs	Foldable legs	Frame opening options	Larger wheelbase	Rough terrain capability	Lift height options	Counterweights	Tyre options	Suspension seat	Turbo diesel engine	Engine heater
<b>M1</b> M1 15.1	s	s	o		o		o	o	o										o	o			
M1 15.3	s	s	o		o		o	o	o										o	o			
M2 20.1	s	s	o		o	o	o	o	o									o	o	o	o	o	
<b>M2</b> M2 20.3	s	s	o		o	o	o	o	o		s		o	o				o	o				
M2 20.4	s	s	o		o	o	o	o	o		s		o	o				o	o				
M3 20.1	s	s			o	o	o	o	o									o	o	o	o	s	o
<b>M3</b> M3 20.3	s	s			o	o	o	o	o		s		o	o				o	o	o	o	s	o
M3 20.4	s	s			o	o	o	o	o		s		o	o				o	o	o	o	s	o
M4 20.1	s	s	o		o	o	o	o	o			o		o				o	o	o	o	o	o
M4 20.3	s	s	o	o	o	o	o	o	o		s		o	o	s	o	o	o	o	o	o	o	o
M4 20.4	s	s	o	o	o	o	o	o	o		s		o	o	s	o	o	o	o	o	o	o	o
<b>M4</b> M4 25.3	s	o	s	o	o	o	o	o	o		s		o	o	o	s	o	o	o	o	o	o	o
M4 25.4	s	o	s	o	o	o	o	o	o		s		o	o	o	s	o	o	o	o	o	o	o
M4 T25.3	s	o	s	o	o	o	o	o	o		s		o	o	s	o	o	o	o	o	s	o	
M4 T25.4	s	o	s	o	o	o	o	o	o		s		o	o	s	o	o	o	o	o	s	o	
M5 20.3	s		o		o	o	o	o	o	o			o			o		s	o	o	o	o	o
<b>M5</b> M5 20.4	s		o		o	o	o	o	o	o			o			o		s	o	o	o	o	o
M5 25.3	s		o		o	o	o	o	o	o								s	o	o	o	o	s
M5 25.4	s		o		o	o	o	o	o	o								s	o	o	o	o	s
M6 25.3	s	o	s	o		o	o	o	o	o	s			o	o	s	o	o	o	o	o	o	o
<b>M6</b> M6 25.4	s	o	s	o		o	o	o	o	o	s			o	o	s	o	o	o	o	o	o	o
M6 T25.3	s	o	s	o		o	o	o	o	o	s			o	o	s	o	o	o	o	o	o	o
M6 T25.4	s	o	s	o		o	o	o	o	o	s			o	o	s	o	o	o	o	o	o	o
M8 25.3	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
M8 25.4	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
<b>M8</b> M8 30.3	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
M8 35.3	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
M8 30.4	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
M8 35.4	s		o	o	o		o	o	o	o		s						s	o	o	o	o	o
<b>M9</b> M9 23.3	s		o		o		o	o	o	o	s			o				s	o	o	o	o	o
M9 24.3	s		o		o		o	o	o	o	s			o				s	o	o	o	o	o

The above can be changed by the manufacturer without prior notice.

s = standard o = optional